



Eco-Friendly



Non-Toxic

ACRYLIC EMULSION

SINOGRACE

The Chemical Company

Architectural Coatings

WF-700 JS cement waterproof emulsion

DESCRIPTION A Suitable for polymer cement waterproofing slurry and polymer cement waterproof sand

TYPE self-crosslinking acrylate copolymer emulsion

KEY FEATURES

- Self - crosslinking acrylic copolymer emulsion
- excellent superhydrophobic properties
- paint film has good low temperature flexibility and tensile strength
- excellent alkali resistance and excellent adhesion with the grassroots level

TYPICAL PROPERTIES

Appearance	Milky white liquid
pH	7-9
Solid content	55%
Glass Transition Temperature	-20°C
Viscosity (25°C)	2500-4000cP
Ionic	anion
Tensile strength	>1.1 MPa
MFFT	0°C
Freeze-Thaw Resistance, 5 cycles	Pass

APPLICATION

- Basecoats
- High-flexibility tile adhesives
- Rigid and flexible waterproofing slurries for sealing in conjunction with tiles and protective surface coatings
- Anticorrosion protection
- Additive for hydraulic binder systems
- Roof coverings

STORAGE AND HANDLING

- Available in 200 kg/ barrel or 25 kg/ barrel
- Store products in tightly closed original containers at 5-40°C
- Shelf life: 9 months from delivery date
- According to non-dangerous goods transport

Anhui Sinograce Chemical Co., Ltd.

Tel: +86-0551-63459511

Email: sales@sinogracechem.com

Add.: Hefei city, Anhui province, China

Mob: +86 15855525589