



**The Chemical Company** 

## Water based Adhesive

## SA-232L Water based pressure adhesive for paper materials

DESCRIPTION	SA-232L is an adhesive specially designed for reverse and various gravure coaters at higher converting speeds, for the production of general purpose paper labels or other pressure sensitive articles.	
ТҮРЕ	Acrylic ester and vinyl ester copolymer dispersion	
KEY FEATURES	<ul> <li>Non-yellowing</li> <li>Wider application range</li> <li>Very good bleeding resistance</li> <li>Very good paper-aging resistance</li> <li>Excellent balance of tack and shear</li> <li>Higher productivity through high speed converting</li> </ul>	
TYPICAL PROPERTIES	Appearance pH Solid content Type of emulsion Viscosity (25°C) Density (20°C)	Milky white liquid 6.0-8.0 54±1% Anionic 200-300mPa·s 1.02 g/cm3
APPLICATION	<ul> <li>General purpose paper labels</li> <li>Various single copper, mirror copper paper, mirror wet paper, thermal paper, mirror aluminum paper, aluminum foil label and advertising materials</li> </ul>	
STORAGE AND HANDLING	<ul> <li>Available in 200 kg/ barrel or 1000 kg/ barrel (IBC)</li> <li>Store products in tightly closed original containers at 5-35°C</li> <li>Shelf life: 6-9 months from delivery date</li> <li>According to non-dangerous goods transport</li> </ul>	