



Eco-Friendly



Non-Toxic

ACRYLIC EMULSION**SINOGRACE**

The Chemical Company

Water-based Acrylic Emulsion

PA-216 Styrene acrylic emulsion for exterior wall top coating

DESCRIPTION

SA-216 exterior wall paint emulsion, excellent water resistance and adhesion,alkali resistance,salt fog resistance, good anti pollution, excellent weather resistance

TYPE

Styrene acrylic copolymer emulsion

KEY

- Strong dilution stability
- Excellent weather resistance

FEATURES

- Excellent scrub resistance
- Excellent adhesion and tinting ability

TYPICAL

PROPERTIES

Appearance	Milky white emulsion
pH	7-9
Solid content	48±1%
Ionicity	Anionic
Viscosity(25°C)	500-2000cPs
MFFT	25°C
Ionic diameter	0.1-0.2µm
TG	27°C

APPLICATION

- Top coating

STORAGE

- 200kg/Plastic Barrel
- Store products in tightly closed original containers at 5-35°C,avoid freezing and high temperature,

AND

HANDLING

- Shelf life: 6 months from delivery date
- According to non-dangerous goods transport

Anhui Sinograce Chemical Co., Ltd.

Tel: +86-0551-63459511

Email: sales@sinogracechem.com

Add.: Hefei city, Anhui province, China

Mob: +86 15855525589