

## Floor care wax coating

### SA-N10 Anti - static floor coating

#### DESCRIPTION

SA-N10 Floor coating is a kind of concentrate floor brightener. It is prepared by scientific formula and strict process with acrylic polymer emulsion and additives.

#### TYPE

Modified Acrylic copolymer dispersion

#### KEY

#### FEATURES

- Leveling: Freely spread on any floor material
- Fast drying: no more than 30 minutes (room temperature)
- High gloss: moderate gloss before polishing, better gloss after polishing
- Wear resistance: it is not easy to leave marks
- Anti-scratch: sufficient hardness and toughness
- Anti-pollution: no dust, easy to clean and maintain
- Anti-slip property: it will not slip when stepped on
- Easy to remove: old wax layer is easy to remove

#### TYPICAL

#### PROPERTIES

<b>Appearance</b>	Milky white liquid
<b>PH</b>	7-8
<b>Solid content</b>	45±1%
<b>Surface resistance</b>	10 <sup>5</sup> -10 <sup>8</sup> ohm
<b>Volume Resistance</b>	10 <sup>5</sup> -10 <sup>8</sup> ohm
<b>Cover area</b>	60-80 m <sup>2</sup> / kg(one layer)
<b>Dilution ratio</b>	1:1

#### APPLICATION

- Wood floor
- Concrete floor
- Epoxy floor
- Plastic compound floor
- PVC and vinyl surface

#### STORAGE

#### AND

#### HANDLING

- Available in 200 kg/ barrel or 25 kg/ barrel
- Store products in tightly closed original containers at 5-40℃
- Shelf life: 9 months from delivery date
- According to non-dangerous goods transport