



Water based Adhesive

SA-228 Water based dry lamination adhesive

DES	CR	TP'	TT	n	N

Water based laminating adhesive for paper and BOPP. It adapts to dry lamination quick drying (tunnel drying). Eco-friendly, non-toxic and excellent comprehensive performance. It can replace solvent based laminating adhesive.

TYPE

Self-crosslinking acrylic polymer dispersion

KEY

- Non-toxic and eco-friendly
- Self-crosslinking acrylic adhesive
- Adapt to high machine speed 60m/min

FEATURES

- Low dosage surface sizing and low cost
- Good brightness, high peel strength, no bubbles, smooth, good toughness

TYPICAL

PROPERTIES

Appearance	Milky white liquid	
pH	5.5-7.0	
Solid content	50±1%	
Type of emulsion	Anionic	
Viscosity (25℃)	100-240mPa s	
Initial adhesive	>14# ball	
Holding power	>24h	
180 °Peel strength	>8N/25mm	

APPLICATION

Lamination of plain films (BOPP, PET, PVC, METPET) to printed paper/duplex board

STORAGE

Available in 200 kg/ barrel or 1000 kg/ barrel (IBC)

AND

Store products in tightly closed original containers at 5-35°C

Shelf life: 6-9 months from delivery date

HANDLING

According to non-dangerous goods transport

Anhui Sinograce Chemical Co., Ltd.

Tel: +86-0551-63459511 Mob: +86 15855525589

Email: sales@sinogracechem.com

Web: www.sinogracechem.com

Add.: Hefei city, Anhui province, China