

## Solid non-phosphate degreaser for sheet and alloy

### MC-DE6660

#### FEATURE

- Biodegradable, non-phosphate degreaser
- Non corrosion effect on the metal surface
- Two-component solid degreaser and alkali degreaser used with surfactant
- Can effectively remove cold rolled steel, cast iron and precision parts surface grease, rust, dust and dirt.

#### APPLICATION

- Appearance: White powder
- Applied temperature: Normal temperature~45°C
- MC-DE6660 applied concentration: 2~4%
- Treatment time: 3~8min
- Treatment way: Dip or spray

#### PROCESS

Add the MC-DE6660 20~40kg into a tank and add the water to 1000L. Then using treat the metal by dipping or spraying. Please remove rust, dust oil and other pollution by overflow or other way in time. It need to supplement the MC-DE6660, when the effect can not meet your request.

**Free alkalinity test method:** Firstly, add 10ml aqueous into an Erlenmeyer flask. Then add 0.1~0.5ml phenolphthalein indicator. Using 0.1mol/L HCl standard solution to titrate it. While the solution changes from red to colorless. The consumption volume of 0.1mol/L HCl standard solution is the free alkalinity value.

#### APPLICATION

- Cold rolled steel, cast iron
- Alloy etc.

#### NOTE

- Please wear the protective gloves when using it.
- MC-DE6660 is acid liquid and wear the protective equipment while using it.
- It contains the phosphate and please treat the waste liquid before discharge.
- Wash immediately with water when skin encounter the cleaning agent.

#### STORAGE AND HANDLING

- Available in 200 kg/ barrel or 25 kg/ barrel
- Storage period: ~12 months in closed containers, shady and dry place