



The Chemical Company

Nano Coatings

9H nano car/ceramic coating (PF-101, 101N, 101S)

	It is a permanent Nano coating that features a high gloss, super
	hydrophobic effect, scratch resistance, UV-resistance, chemical
	resistance, thermal resistance and anti-grafitti. The technical
DESCRIPTION	formulation has enabled it to be multi-layered which means the
	thickness of the coating can be increased with additional layers
	allowing a thicker/harder film that will increase its scratch
	resistance.

ТҮРЕ	Car self-cleaning nano coating			
KEY FEATURES	 Anti-Graffiti High Gloss Finish Scratch Resistance Permanent Protection Super Hydrophobic Effect 	• • •	Weather&UV Resistance Advanced Chemical Resistance Oxidation&Corrosion Resistant Thermal Resistance (up to 750°C)	

	Туре	PF-101N	PF-101	PF-101S	
	Appearance	Clear / Candy Gloss			
	Gloss	****	****	****	
TYPICAL	Hardness	6-7H	7-8H	9H	
	Scratch resistance	****	****	****	
PROPERTIES	Hydrophobic effect	****	****	****	
	Duration	2-3 years	2-3 years	3-5 years	
	Temp. resistance	> 750 ℃	> 750 ℃	> 750 ℃	
	Coverage (1-layer)	60 sqft / ounce (30 ml)			

APPLICATION Car paint

• Ceramic, glass, metal etc.

STORAGE

- Available in 30ml/bottle, 1L/ barrel or customized package
- Store products in tightly closed original containers at $0-35^{\circ}$ C
 - Shelf life: 12-18 months from delivery date

HANDLING

AND

Anhui Sinograce Chemical Co., Ltd.Add.: Hefei city, Anhui province, ChinaTel: +86-0551-63459511Email: sales@sinogracechem.comWeb: www.sinogracechem.comWeb: www.sinogracechem.com



SIN[©]GRACE

The Chemical Company

Video link: https://www.youtube.com/watch?v=EAP-WsoNg54

Step 1: Cleaning and Polishing

• Polish the car paint to remove the scratch; Degreasing to remove the oil and residue on car paint, to make coating be tightly attached on car paint.

Step 2: Wipe Coating by Sponge

• Put the coating on sponge and coating small area by area as "T" shape on car paint.

Step 3: Wipe by Microfiber Cloth

1-2 minutes later, the finger feel coating be sticky without spare water left, then wipe by the microfiber towel which twisted from water. Wipe again and again repeatedly until looks shinny. About 1 hour later, coating solidity, the first layer of coating finished. If operating the second layer of coating, you can do same as the first layer.

Caution:

- After coating finished on car paint, the car can be used after 3 hours later without rainy day. 72 hours later you can wash the car, 20 days later the coating get the best effect.
- Within 72 hours after finished with coating, should better not attach water on car paint. If water attached, wipe it be dry right away, to avoid print occur.
- Within 72 hours, should better not drive the car too fast, if the objects such as mosquito attached on, clean the dirt right away.



Anhui Sinograce Chemical Co., Ltd. Tel: +86-0551-63459511 Email: <u>sales@sinogracechem.com</u> Add.: Hefei city, Anhui province, China

Web: www.sinogracechem.com

HOW TO USE